



## UTS 400 USB to Serial Port Converter

- ◆ **Support four ports in one box**
- ◆ **Support four RS232 ports**
- ◆ **Powerful and Flexible for redundancy usage**



- Support USB2.0 device controller
- 512 Bytes FIFO for data transfer
- Support LED display for each port
- four RS232 for local connection
- Support bus power red mode
- Use MOSCHIP MCS7840 chip

<b>UTS400 Specification :</b>	
<p><b>USB interface:</b></p> <ul style="list-style-type: none"> <li>*Connector type: USB B type connector.</li> <li>*Device Controller: USB 2.0</li> <li>*stream FIFO size: 512Byte per serial port.</li> </ul> <p><b>RS232 interface:</b></p> <ul style="list-style-type: none"> <li>*Connector type: DB9 male connector.</li> <li>*Number of ports: 4 (port A,B,C,D)</li> <li>NOTE: port A,B,C,D have same signal ground with power input from USB bus.</li> </ul> <p><b>Environment :</b></p> <ul style="list-style-type: none"> <li>*operating temperature: 0v to 35.</li> <li>*operating humidity: 10% to 95% RH.</li> <li>*storage temperature: 0 to 65°C.</li> <li>*storage humidity: 5% to 95% RH.</li> </ul> <p><b>Dimension :</b></p> <p>*UTS400 box: 90mm (W) * 150mm (L) * 27mm(H)</p>	<p><b>LED indicator:</b></p> <ul style="list-style-type: none"> <li>*PWR: DC power input ON indicator.</li> <li>*ATRD: RS232 port A TXD/RXD signal activity.</li> <li>*BTRD: RS232 port B TXD/RXD signal activity.</li> <li>*CTRD: RS232 port C TXD/RXD signal activity.</li> <li>*DTRD: RS232 port D TXD/RXD signal activity.</li> </ul> <p><b>Power input:</b></p> <ul style="list-style-type: none"> <li>*USB bus powered mode.</li> <li>*Current consumption: 200mA @ 5VDC.</li> <li>NOTE: user can order UTS400S for self-power mode to work with 5VDC power adapter</li> </ul> <p><b>Accessories:</b></p> <ul style="list-style-type: none"> <li>*U101 cable: 6 feet USB A type to B type connector.</li> </ul>

<b>Performance upgrade capability and relative products :</b>
*TWIN485 box: two port ground isolated RS232 to RS422/485 converter.
*UTS040 box: USB to four ground isolated RS232 ports.
*UTS004 box: USB to four ground isolated RS422/485 ports.
*UTS485 box: USB to two RS232 and two ground isolated RS422/485 ports.
***All names are the trademarks of their respective organization.

Note : All the technical and commercial specifications of the product displayed within the brochure, box, media, color, price, etc. are subject to change without any prior notice. No claims would be entertained by Pushpam and/or its principal vendors in this regards. For all technical and commercial matter, jurisdiction would be Pune city only.

**Pushpam Group of Companies**

**Pushpam Computers & Softwares**

**Pushpam Infotech Corp.**

**Pushsoft Technologies**

635/1-B, New Gajra Society, Bibwewadi, Pune - 411037  
 Tel. No. 91+20+3091 506 /931/ 934  
 Fax: 91+20+24216455  
 Email: dealersales@pushpam.com, sales@pushpam.com,  
 rahul\_jangam@pushpam.com

Pushpam a 15 year old group is working in the various fields of Information Technology . Software development, Gas distribution, Computer hardware imports/ distribution , manufacturing of ayurvedic medicines, food processing and export etc. Working in cutting edge technology products, Pushpam always aggressive and efficient towards all the projects. In IT sector Pushpam is active since last 14 years and is currently working on technologies like Information Kiosk / Transaction Kiosk /Touch screens, POS products like Thermal printers, barcode scanners, Customer display, complete POS systems and Multi port serial card solutions. Pushpam is already in to imports of all these products from Taiwan and other parts of the world and offers the complete solution and best support for all these products. Pushpam has always believed in the best product and best support at the best price.

